

Dräger Polytron 2 XP Ex Fixed Gas Detector

The Dräger Polytron 2 XP Ex is an explosion proof gas detector for continuous monitoring of combustible gases and vapors in ambient air. The transmitter converts the signal from a catalytic bead or IR sensor to a 4 to 20 mA analog or HART® or RS 485 digital signal output.



The unit is designed for one-man calibration, and offers a variety of diagnostics and self test features. The configuration and calibration of the transmitter is menu guided and easy to perform.

ONE MAN CALIBRATION

All setup and maintenance can be performed without opening the transmitter or declassifying the hazardous area. An infrared remote control, beaming through the window, gives full access to the menu and calibration procedure. The menu can also be accessed using the built-in push buttons or a HART® hand held terminal. All menu items and messages are displayed in plain English. Other, user selectable languages are French, Spanish and German.

DRÄGERSENSOR TECHNOLOGY

Dräger Polytron 2 XP Ex offers two sensing principles: catalytic combustion or infrared. The interior design of the catalytic bead sensor offers an extremely high sensitivity. Higher sensitivity also means shorter response times, higher accuracy and improved stability of the sensor signal. The advanced poison resistant DrägerSensor PR has a significantly longer lifetime.

The DrägerSensor IR is the sensor of choice, where 'poisonous' gases might be in the ambient air. Over time, these can damage the catalyst of a catalytic bead sensor, decreasing its sensitivity. In order to reduce maintenance costs for recalibration and exchange, the infrared technology offers a superior solution.

STAND ALONE SYSTEM

With the three built-in relays, Dräger Polytron 2 XP Ex can be used as an independent stand alone unit. Two adjustable gas alarm levels and a fault alarm make it convenient to switch warning devices on-site, without having to run cables back and forth to a central controller. The sensor signal can still be transmitted using either the 4 to 20 mA, HART® or RS 485 signal output.

FEATURES/BENEFITS

- Poison resistant catalytic bead sensor
- High performance infrared sensor
- Fast, accurate response
- Non-intrusive calibration
- Backlit LC-Display
- 4 to 20mA, HART®, RS 485 interface
- Multidrop capability, reduced wiring costs
- Optional relays on board
- ATEX, UL and CSA approved

ST1390-2006



Dräger Polytron 2 XP Ex
Catalytic bead sensor to detect combustible gases and vapors.

ST1388-2006



Dräger Polytron 2 XP Ex IR
DrägerSensor IR to detect combustible gases and vapors.

TECHNICAL DATA

Type	Explosion proof transmitter		
Gases and Ranges	Combustible gases and vapors; 0 to 100 %LEL		
Display	Backlit LCD; 2 lines, 20 characters; resolution 1 %LEL		
Output Signal	Menu structure and messages in real text		
Relays (optional)	Analog	Normal operation	4 to 20 mA
		Warning, configurable	fault signal every 10 s for 1 s, or off; user programmable
		Maintenance	4 ± 1 mA 1 Hz modulation, or steady; user programmable
		Fault	< 1.2 mA
		Digital	HART®, RS 485
Supply Voltage	Two alarm relays, one fault relay SPDT; user programmable Rating: 5A 230 VAC, 5A 30 VDC		
Ambient Conditions	10 to 32 VDC, 3-wire		
Enclosure	Temperature	40 to + 175 °F / - 40 to + 80 °C *	
		40 to + 150 °F / - 40 to + 65 °C **	
	Pressure	20.7 to 38.4 inch Hg / 700 to 1300 mbar	
	Humidity	0 to 100 %RH	
Size (h x w x d, approx.)	NEMA 4X & 7, IP 66; 3/4" NPT female conduit entry		
Weight (approx.)	7" x 5" x 5" / 180 x 130 x 130 mm *, 12" x 5" x 5" / 305 x 130 x 130 mm **		
Approvals	UL, CSA	Class I, Div 1, Group B, C, D *	
		Class I, Div 1, Group B, C, D; Class II, Div 1, Group E, F, G **	
	ATEX	II 2G EEx d IIC T6/T4, II 2D T85/T135°C; - 40 ≤ Tamb ≤ + 40 / + 80 °C *	
		II 2G EEx d IIC T6/T4, II 2D T85/T135°C; - 40 ≤ Tamb ≤ + 40 / + 65 °C **	
	CE-mark	electromagnetic compatibility (directive 89/336/EEC)	

* with catalytic bead sensor

** with IR sensor

HART® is registered trademark of HCF, Austin, TX

ORDER INFORMATION

Dräger Polytron 2 XP Ex with catalytic bead sensor, without relays; UL version	45 43 005
Dräger Polytron 2 XP Ex with catalytic bead sensor and relays; UL version	45 43 000
Dräger Polytron 2 XP Ex with catalytic bead sensor, without relays; ATEX, CSA	45 43 060
Dräger Polytron 2 XP Ex with catalytic bead sensor and relays; ATEX, CSA	45 43 059
Dräger Polytron 2 XP Ex with IR sensor, without relays; UL version	45 43 223
Dräger Polytron 2 XP Ex with IR sensor and relays; UL version	45 43 224
Dräger Polytron 2 XP Ex with IR sensor, without relays; ATEX version	45 43 227
Dräger Polytron 2 XP Ex with IR sensor and relays; ATEX version	45 43 229
Dräger Polytron 2 XP Ex with IR sensor without relays; CSA version	45 43 234
Dräger Polytron 2 XP Ex with IR sensor and relays; CSA version	45 43 236

HEADQUARTERS:

Dräger Safety AG & Co. KGaA
Revalstrasse 1
23560 Lübeck, Germany

www.draeger.com

SYSTEM CENTERS:

P. R. CHINA

Beijing Fortune Draeger Safety
Equipment Co., Ltd.
A22 Yu An Rd, B Area,
Tianzhu Airport Industrial Zone,
Shunyi District,
Beijing 101300
Tel +86 10 80 49 80 00
Fax +86 10 80 49 80 05

GERMANY

Dräger Safety AG & Co. KGaA
Revalstrasse 1
23560 Lübeck
Tel +49 451 882-2794
Fax +49 451 882-4991

FRANCE

Dräger Safety France SAS
3c route de la Fédération, BP 80141
67025 Strasbourg Cedex 1
Tel +33 3 88 40 59 29
Fax +33 3 88 40 76 67

SINGAPORE

Draeger Safety Asia Pte Ltd
67 Ayer Rajah Crescent #06-03
Singapore 139950
Tel +65 68 72 92 88
Fax +65 65 12 19 08

UNITED KINGDOM

Draeger Safety UK Ltd.
Blyth Riverside Business Park
Blyth, Northumberland NE24 4RG
Tel +44 1670 352 891
Fax +44 1670 544 475

USA

Draeger Safety, Inc.
505 Julie Rivers, Suite 150
Sugar Land, TX 77478
Tel +1 281 498 10 82
Fax +1 281 498 51 90